## PARABIT DUO ANGLE REINFORCING STRIP

Parabit Duo Angle Reinforcing Strip is used to locally reinforce junctions and angles in the Parabit Hot Melt membrane where there is a change in substrate type, (concrete slab to masonry upstands). Membranes should be installed in accordance with the manufacturer's guidelines..



Cha	aracteristics
Length	20 m
Width	0.300 m
Material Type	SBS-Modified Bitumen
Thickness	1.7mm
Gross Weight	0.300kg /m2



\* The external fire performance is a system test, please contact BMI lcopal Technical Services to verify that the chosen system has the potential to meet your required performance prior to commencement.

### PACKAGING

Description	Roll Size Rolls per	pallet
PARABIT DUO ANGLE REINFORCING STRIP	0.3m x 20m 25 Ro	II

#### **STORAGE**

Materials for reinforced bitumen membrane roofing should be stored upright on clean dry level surfaces, undercover and clear of the ground. The same protection should be given to materials temporarily kept outdoors or on the roof during construction. Storage temperatures should be between 0°C and 30°C. Refer to BS 8000-4 (Section 2.1.2.2) for further information.

#### **INSTALLATION SUMMARY**

For further details please consult our Flat Roofing Product Installation Guidelines or contact our BMI Icopal technical services team.

#### **TECHNICAL SERVICES**

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585 E: technical.uk@bmigroup.com

# Œ

#### SAFETY, QUALITY & ENVIRONMENT

BMI Icopal membranes are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.





ISO 9001:2015 44 100 21410102 ISO 14001:2015 44 100 21410102



BMI Group UK Limited BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI lcopal technical services team.