

# PARABIT HOT-MELT -COMPOUND

Parabit Hot Melt Compound is intended for use with a reinforcement and protection sheet to create a waterproofing membrane specifically developed for use on inverted, green and plaza deck roofs. Membranes should be installed in accordance with the manufacturer's guidelines.



Characteristic	
Weight	11 kg
Material Type	SBS Modified Bitumen
Base Unit of Measure	PCE
Uniclass Reference	Pr 20_31_02_37

## PACKAGING

Description	Contents	Boxes per pallet	
Parabit Hot Melt Compound	11.0 Kg	48	

## STORAGE

Materials for reinforced bitumen membrane roofing should be stored upright on clean dry level surfaces, undercover and clear of the ground. The same protection should be given to materials temporarily kept outdoors or on the roof during construction. Storage temperatures should be between 0°C and 30°C. Refer to BS 8000-4 (Section 2.1.2.2) for further information.

## INSTALLATION SUMMARY

For further details please consult our Flat Roofing Product Installation Guidelines or contact our BMI Icopal technical services team.

## TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: [technical.uk@bmigroup.com](mailto:technical.uk@bmigroup.com)



## SAFETY, QUALITY & ENVIRONMENT

BMI Icopal membranes are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet.



ISO 9001:2015  
44 100 21410102



ISO 14001:2015  
44 100 21410102



### BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW  
[bmigroup.com/uk](http://bmigroup.com/uk)

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.