

## FF817 Bitumen Primer

### Product Description

A low viscosity, high penetration, cold applied bituminous solution designed to prime and seal porous roof surfaces prior to the application of bituminous materials. FF817 Bitumen Primer seals porous substrates and promotes the adhesion of bituminous waterproofing systems and sheet coverings. It may be applied to a range of surfaces:

- Concrete
- Asbestos cement
- Metals: mild steel, zinc & lead
- Slate, lightweight concrete screeds

### Colour

Black

### Method of Application

FF817 Bitumen Primer should be applied by brush ensuring an even coat with no pooling, or applied evenly by airless spray.

### Instructions

Care needs to be taken over preparation of surfaces before application. All surfaces must be free from oil, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire brush and where advanced signs of corrosion are evident the area be treated with a rust inhibitor. Surfaces should be dry for best results, although FF817 Bitumen Primer will adhere to damp but not wet surfaces. FF817 Bitumen Primer is resistant to rainfall within 20 to 30 minutes of application.

### Coverage

The coverage per litre is dependent upon the porosity of the surface.

Substrate	Coverage rate	Coverage per 25 litre tin
Metal	6 m <sup>2</sup> to 12 m <sup>2</sup> per litre	150 m <sup>2</sup>
Concrete	6 m <sup>2</sup> to 8 m <sup>2</sup> per litre	150 m <sup>2</sup>
Plywood, lightweight concrete screeds and asbestos cement	3.5 m <sup>2</sup> to 5 m <sup>2</sup> per litre	87.5 m <sup>2</sup>

### Cleaning Tools

Tools may be cleaned with white spirit. Minor spillages should be wiped off surfaces immediately before the product has set. Major spillages should be mopped up immediately with an inert, absorbent material, such as sand and disposed of in accordance with regulations.

### Container Size

25 litre

**VOC Details**

EU Limit for this product CAT. 2(h): 750g/l (2010). This product contains max. 450g/l VOC's.

**Storage**

Indefinite in undamaged, tightly sealed containers. Containers must be kept sealed and stored away from sources of heat and ignition.

**Health & Safety**

Please refer to health & safety data sheet on FF817 Bitumen Primer.

**Further Information**

In the event of further queries or problems concerning the use of this product, please e-mail [technical@fatra.co.uk](mailto:technical@fatra.co.uk)

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control.