

## FF854 PVC Liquid Sealant

### Product Description

Fatra FF854 PVC Liquid Sealant to be used in association with Fatra membranes. FF854 PVC Liquid Sealant only needs to be used on site-cut edges of FF810 Membrane.



### Application

All surfaces must be dry and free of dirt, oil grease, etc. If necessary wipe clean. Ensure that the sealant is at a temperature of between 55°F and 86°F, to facilitate proper adhesion characteristics. Stir well before use. Do not allow water to get into sealant. Apply to seams only by means of special applicator to ensure a good even cover.

### Storage

Maximum of 12 months in well sealed containers. Low and high temperature storage should be avoided to achieve proper spreading the adhesive should be stored between 55°F and 86°F. Fatra FF854 contains highly flammable solvents and must be stored in well-ventilated dry areas.

### Environmental and Waste Controls

Dry residues may be disposed of as industrial waste. Liquid residues should be disposed of as hazardous waste.

### Physical Characteristics

| FF854 PVC Liquid Sealant |                    |
|--------------------------|--------------------|
| Appearance               | Grey liquid        |
| Base                     | Tetrahydrofuran    |
| Flammability             | Highly Inflammable |
| Dilatants                | n/a                |
| Cleaner                  | n/a                |
| Shelf Life               | 12 months          |

Full details on separate Safety Data Sheet for this product.