



**ZETTEX**

STICK WITH US

## TECHNICAL DATA SHEET

### Spraybond X100 Aerosol

**Zettex Europe B.V.**

Plaza 20, 4782 SK Moerdijk

The Netherlands

+31 (0)888-93 88 39

[info@zettex.com](mailto:info@zettex.com)

[www.zettex.com](http://www.zettex.com)

#### Product description

Zettex Spraybond X100 Foambond is a one component polyurethane foam adhesive for the adhering of EPS, XPS, PUR, PU, mineral insulation materials, mineral wool, stone wool, cork and other foams. Due to the high initial adhering, you can use the Spraybond X100 Foambond on wall insulation systems as well.

#### Material

Polyurethane

#### Benefits

- Very fast curing time: around 1 hour.
- Wind resistant, tested by BDA.
- Ideal for the renovation of bituminous roofs.
- Flexible.
- Extremely economical in use, precise dosing is possible.
- Solvent-free, do not dissolve polystyrene (EPS).
- Avoid creating cold bridges.
- Non-Flammable

#### Applications

- You can apply Zettex Spraybond X100 Foambond on bituminous roofs. The vertical adhering is possible as well.
  - In addition, it can also be applied to stainless steel plates, concrete, fiber cement and concrete concrete.
  - Application possible on wood, hard PVC, plaster and bitumen, but not applicable to PE, PTFE and PP.
- Besides, we recommend you to do a test before you start the adhering. So, you can test the surface to be treated and know the quality of the adhering.

#### Certificates



Properties	Specifications
Application temperature	+5 to +40 degrees
Consumption	12 m <sup>2</sup>
Open time	Max 6 minutes, walkable after 20 minutes
Total curing time	1 hour
Durability	18 months, if stored in an unopened packaging at temperatures between 5 and 25 degrees.